



Optional

Made in Democratic Taiwan



300 g x 0.1 g  
 600 g x 0.2 g  
 1,500 g x 0.5 g  
 3,000 g x 0.5 g  
 6,000 g x 1 g  
 12 kg x 0.002 kg  
 30 kg x 0.005 kg



Models:  
AGS 300-600  
Round Pan

- ALL STAINLESS STEEL WASHDOWN
- IDEAL PORTION WEIGHER
- RECHARGEABLE BATTERY & POWER ADAPTER
- READS IN: G, LB, OUNCES
- HEAVY DUTY
- LOW PROFILE
- 3 COLOR LCD FOR CHECK WEIGH
- RS232 INTERFACE



Class III

PART NUMBER	AGS-300BL	AGS-600BL	AGS-1500BL	AGS-3000BL	AGS-6000BL	AGS-12KBL	AGS-30KBL
Capacity	150 g / 300 g / 0.66 lb	300 g / 600 g / 1.32 lb	600 g / 1500 g / 3.3 lb	3000 g / 6.6 lb	6000 g / 13.2 lb	12 kg / 26.4 lb	30 kg / 66 lb
Readability	0.05 g / 0.1 g / 0.00002 lb / 0.005 oz (non-NTEP 0.01g)	0.1 g / 0.2 g / 0.0005 lb / 0.005 oz (non-NTEP 0.02g)	0.2 g / 0.5 g / 0.002 lb / 0.02 oz (non-NTEP 0.05g)	0.5 g / 0.002 lb / 0.02 oz (non-NTEP 0.1g)	1 g / 0.005 lb / 0.05 oz (non-NTEP 0.2g)	0.002 kg / 0.005 lb / 0.1 oz (non-NTEP 0.5g)	0.005 kg / 0.02 lb / 0.2 oz (non-NTEP 0.001kg)
Divisions	3,000			6,000			
Weighing Units	Kg, lb, g, oz, lb;OZ					Kg, lb, g, oz, lb;OZ	
Functions	Accumulation						
Stabilization Time	< 1.5 seconds						
Tare Range	To capacity by subtraction						
Power Source	Built-in rechargeable battery or external power adapter (included)						
Construction	Stainless steel pan & housing						
Display	0.75 inch / 19 mm wide viewing angle 3 color backlit LCD						
Pan Size (W x D)	5.75 inches / 146 mm diameter		8.25 x 8.25 inches / 210 x 210 mm				
Dimensions (W x D x H)	9.1 x 12.2 x 3 inches / 230 x 310 x 75 mm						
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%						
Connectivity	RS232 Port						
Net Weight	8.15 lb / 3.7 kg						
Shipping Weight	12.3 lb / 5.6 kg						
NEMA / IP Rating	IP 65						
Options	Carrying Case						
Approvals	NTEP C.o.C. #18-130						

High resolution is only available in “normal” setting. Not NTEP approved.

FEATURES	BENEFITS
All stainless steel housing & pan	Easy to clean for food processing or harsh environments
Heavy duty construction	Will withstand harsh industrial operation
Sealed electronics	Improved water & dust resistance
Low profile, compact size	Uses less counter space
Reads in grams, pounds, & ounces	Flexibility of operation
Built-in rechargeable battery or external power adapter	Portability - battery lasts a minimum of 150 hours (w/out backlight)
Accumulation function	Allows you to add together consecutive weights to arrive at a total
Zero tracking	Ensures that you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Adjustable stainless steel feet w/ rubber inserts	Scale remains level for accurate results on uneven working surfaces - anti-slip
Wide-angle LCD display w/ backlight	Can be seen from a wide viewing range