



Made in Democratic Taiwan



3,000 g x 0.05 g
6,000 g x 0.1 g
30 kg x 0.5 g
60 kg x 0.001 kg



- SAVE UP TO 10 PRODUCT MEMORIES
- 3 COLOR HI-LO-GO LIGHT TOWER INCLUDED
- AUDIBLE & VISUAL ALARMS
- DIRECT TARE ENTRY W/ 10-KEY PAD
- RS232 DATA TRANSFER

PART NUMBER	SEK-3K	SEK-6K	SEK-30K	SEK-60K
Capacity	6.6 lb / 3,000 g	13.2 lb / 6000 g	66 lb / 30 kg	132 lb / 60 kg
Readability	0.05 oz / 0.05 g	0.01 oz / 0.1 g	0.02 oz / 0.5 g	0.1 oz / 0.001 kg
Displayed Divisions	1/60,000, 1/30,000 or 1/15,000 (configurable)			
Internal Counting Resolution	1,000,000			
Weighing Units / Functions	Kg, lb, lb,OZ, g, Piece Counting, Checkweighing			
Stabilization Time (Seconds)	< 3			
Tare Range	To capacity by subtraction			
Maximum Zero Range	2% of rated capacity			
Power Source	120V A/C external power cord (included)			
Construction	Stainless steel pan & ABS housing			
Display	1" / 25 mm wide viewing angle backlit LCD			
Pan Size (W x D)	7" x 11.5" / 292 x 178 mm	13.6" x 9" / 345 x 230 mm		
Connectivity	RS 232 interface			
Dimensions (W x D x H)	14.2 x 14.2 x 4.5 inches / 360 x 360 x 114 mm (Tower height: 24" from base of scale)			
Operating Environment	32° ~ 104° F non-condensing R.H. ≤ 85%			
Net Weight	13 lb / 5.9 kg			
Shipping Weight	17 lb / 7.8 kg			

FEATURES	BENEFITS
Memory Save Function	Ensures consistent HI-LO-GO weighing for up to 10 individual product memories
HI-LO-GO Check status indicator / Programmable audio output	Ideal for portion control, checkweighing or counting - ensures fast throughput w/ fewer mistakes
Power-on zero tracking	Ensures that you always start weighing at zero
Digital motion filter at zero & weighing	Automatically adjusts for adverse environmental conditions
Auto-calibration functions	Ensures accuracy
RS 232 interface	Allows communication w/ peripheral data collection & printing instruments
Easy to use keyboard arrangement	Makes training & operation simple, reducing mistakes
100% subtractive tare	Enables the weight of containers to be ignored
Large, bright backlit display	Easy to read in all lighting conditions including bright sunlight
Adjustable feet / spirit level	The scale remains level for accurate results even on uneven working surfaces